

Anvil Compliances, Listings and Approvals

Anvil Figure Number	Product Types			Application Sizes					
	MSS-SP-58 & MSS-SP-69	Federal Specifications		FM* Rod Size	FM* Pipe Size	UL■ Rod Size	UL■ Pipe Size	ULC▲ Rod Size	ULC▲ Pipe Size
		WW-H-171-E	A-A-1192A						
14	27	54	27	-	-	-	-	-	-
40	42	-	42	-	-	-	-	-	-
45	-	-	-	-	-	-	-	-	-
46	-	-	-	-	-	-	-	-	-
47	-	-	-	-	-	-	-	-	-
49	-	-	-	-	-	-	-	-	-
50	-	-	-	-	-	-	-	-	-
52	-	-	-	-	-	-	-	-	-
54	-	-	-	-	-	-	-	-	-
55	57	57	57	-	-	-	-	-	-
55L	57	57	57	-	-	-	-	-	-
60	-	-	-	-	-	-	-	-	-
62	-	-	-	-	-	-	-	-	-
63	-	-	-	-	-	-	-	-	-
65	-	12	-	1/2	2 1/2 - 4	1/2	2 1/2 - 4	-	-
66	22	22	22	-	-	-	-	-	-
67	5	-	5	-	-	-	-	-	-
69	10	10	10	3/8	3/4 - 4	3/8	3/4 - 4	3/8	3/4 - 4
				1/2	5 - 8	1/2	5 - 8	1/2	5 - 8
86	23	23	23	3/8	3/4 - 2	3/8	3/4 - 2	3/8	3/4 - 2
				-	-	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
				-	-	5/8	4, 5	5/8	4, 5
				-	-	3/4	6	3/4	6
87	23	23	23	3/8	3/4 - 2	3/8	3/4 - 2	3/8	3/4 - 2
				-	-	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
				-	-	5/8	4, 5	5/8	4, 5
				-	-	3/4	6	3/4	6
88	23	23	23	3/8	3/4 - 2	3/8	3/4 - 2	3/8	3/4 - 2
				-	-	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
				-	-	5/8	4, 5	5/8	4, 5
				-	-	3/4	6	3/4	6
89	-	-	-	-	-	-	-	-	
89X	-	-	-	-	-	-	-	-	-
92	19 & 23	23	19 & 23	3/8	3/4 - 4	3/8	2 1/2 - 4	3/8	2 1/2 - 4
				1/2	5 - 8	1/2	5 - 8	1/2	5 - 8
93	19 & 23	23	19 & 23	3/8	3/4 - 4	3/8	2 1/2 - 4	3/8	2 1/2 - 4
				1/2	5 - 8	1/2	5 - 8	1/2	5 - 8
94	19	19	19	5/8	10	5/8	10	-	-
				3/4	12	3/4	12	-	-
95	23	23	23	-	-	-	-	-	-
97	9	9	9	3/8	3/4 - 2	3/8	3/4 - 2	-	-
				1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2	-	-
				5/8	4	5/8	4	-	-
97C	9	9	9	-	-	-	-	-	-
100	-	-	-	-	-	-	-	-	-
103	-	-	-	-	-	-	-	-	-
104	6	6	6	-	-	-	-	-	-
108	11	11	11	-	-	-	-	-	-
110R	16	16	16	3/8	3/4 - 4	3/8	3/4 - 4	-	-
				1/2	5 - 8	1/2	5 - 8	-	-
				5/8	10	5/8	10	-	-
				3/4	12	3/4	12	-	-
				7/8	12	7/8	12	-	-

* = FM Approved ■ = UL Listed ▲ = ULC Listed

Anvil Compliances, Listings and Approvals

(cont.)

Anvil Figure Number	Product Types			Application Sizes					
	MSS-SP-58 & MSS-SP-69	Federal Specifications		FM* Rod Size	FM* Pipe Size	UL■ Rod Size	UL■ Pipe Size	ULC▲ Rod Size	ULC▲ Pipe Size
		WW-H-171-E	A-A-1192A						
112	-	-	-	-	-	-	-	-	-
113	-	-	-	-	-	-	-	-	-
114	15	15	15	-	-	-	-	-	-
120	-	-	-	-	-	-	-	-	-
126	-	-	-	-	-	-	-	-	-
127	-	-	-	-	-	-	-	-	-
128	-	-	-	-	-	-	-	-	-
128R	-	-	-	-	-	-	-	-	-
133	21	21	21	-	-	3/8	3/4 - 4	-	-
				-	-	1/2	5 - 8	-	-
134	21	21	21	1/2	5 - 8	1/2	5 - 8	-	-
				5/8	10 - 12	5/8	10 - 12	-	-
135	-	-	-	-	-	-	-	-	-
135E	-	-	-	-	-	-	-	-	-
135R	-	-	-	-	-	-	-	-	-
136	-	-	-	3/8	3/4 - 4	3/8	3/4 - 2	3/8	3/4 - 2
	-	-	-	1/2	5 - 8	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
	-	-	-	-	-	5/8	4, 5	5/8	4, 5
	-	-	-	-	-	3/4	6	3/4	6
	-	-	-	-	-	7/8	8	7/8	8
136R	-	-	-	-	-	-	-	-	-
137	24	24	24	-	-	-	-	-	-
137C	24	24	24	-	-	-	-	-	-
137S	-	-	-	-	-	-	-	-	-
138R	12	25	12	-	-	-	-	-	-
140	-	-	-	-	-	-	-	-	-
142	-	-	-	-	-	-	-	-	-
146	-	-	-	-	-	-	-	-	-
148	-	-	-	-	-	-	-	-	-
152	-	-	-	3/8	3/4 - 2	3/8	3/4 - 2	3/8	3/4 - 2
	-	-	-	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
	-	-	-	5/8	4, 5	5/8	4, 5	5/8	4, 5
	-	-	-	3/4	6	3/4	6	3/4	6
	-	-	-	7/8	8	7/8	8	7/8	8
153	-	-	-	3/8	3/4 - 2	3/8	3/4 - 2	3/8	3/4 - 2
	-	-	-	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
	-	-	-	5/8	4, 5	5/8	4, 5	5/8	4, 5
	-	-	-	3/4	6	3/4	6	3/4	6
157	-	-	-	3/8	3/4 - 4	3/8	3/4 - 2	-	-
	-	-	-	1/2	5 - 8	1/2	2 1/2 - 3 1/2	-	-
	-	-	-	-	-	5/8	4, 5	-	-
	-	-	-	-	-	3/4	6	-	-
160	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
161	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
162	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
163	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
164	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
165	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
165A	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
166A	39A & 39B	40A & 40B	39A & 39B	-	-	-	-	-	-
167	40	41	40	-	-	-	-	-	-
168	40	41	40	-	-	-	-	-	-
171	41	42	41	-	-	-	-	-	-
175	44	45	44	-	-	-	-	-	-
177	41	42	41	-	-	-	-	-	-
178	49	50	49	-	-	-	-	-	-

* = FM Approved ■ = UL Listed ▲ = ULC Listed

Anvil Compliances, Listings and Approvals

(cont.)

Anvil Figure Number	Product Types			Application Sizes					
	MSS-SP-58 & MSS-SP-69	Federal Specifications		FM* Rod Size	FM* Pipe Size	UL■ Rod Size	UL■ Pipe Size	ULC▲ Rod Size	ULC▲ Pipe Size
		WW-H-171-E	A-A-1192A						
181	43	44	43	-	-	-	-	-	-
191	37	38	37	-	-	-	-	-	-
192	38	39	38	-	-	-	-	-	-
194	31	32	31	3/8	3/4 - 4	-	-	-	-
				1/2	5 - 8	-	-	-	-
				-	-	-	-	-	-
				-	-	-	-	-	-
				-	-	-	-	-	-
195	32	33	32	-	-	-	-	-	
199	33	34	33	-	-	-	-	-	
202	34	35	34	3/8	3/4 - 4	3/8	3/4 - 2	3/8	3/4 - 2
				1/2 (Steel beam)	5 - 8	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
				-	-	5/8	4, 5	5/8	4, 5
206	34	35	34	3/8	3/4 - 4	3/8	3/4 - 4	-	-
				1/2	5, 6	1/2	5, 6	-	-
				5/8	8	5/8	8	-	-
207	34	35	34	3/8	3/4 - 4	3/8	3/4 - 4	-	-
				-	-	1/2	5 - 8	-	-
212	4	4	4	3/8	3/4 - 2	3/8	3/4 - 2	3/8	3/4 - 2
				1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
				5/8	4, 5	5/8	4, 5	5/8	4, 5
				3/4	6	3/4	6	3/4	6
				7/8	8	7/8	8	7/8	8
212FP	4	4	4	-	-	-	-	-	-
216	4	4	4	-	-	-	-	-	-
217	25	-	25	-	-	-	-	-	-
218	30	30	30	3/8	3/4 - 4	3/8	3/4 - 2	3/8	3/4 - 2
				-	-	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
				-	-	5/8	4, 5	5/8	4, 5
				-	-	3/4	6	3/4	6
				-	-	7/8	8	7/8	8
224	2	2	2	-	-	-	-	-	-
227	25	-	25	3/8	3/4 - 2	3/8	3/4 - 2	-	-
		-		-	1/2	2 1/2 - 8	-	-	
228	28 & 29	30 & 31	28 & 29	-	-	-	-	-	-
228L	28 & 29	30 & 31	28 & 29	-	-	-	-	-	-
230	13	13	13	-	-	-	-	-	-
233	13	13	13	-	-	-	-	-	-
243	-	-	-	-	-	-	-	-	-
244	-	-	-	-	-	-	-	-	-
246	2	2	2	-	-	-	-	-	-
248	-	-	-	-	-	-	-	-	-
248L	-	-	-	-	-	-	-	-	-
248X	-	-	-	-	-	-	-	-	-
253	-	-	-	-	-	-	-	-	-
255	-	-	-	-	-	-	-	-	-
256	-	-	-	-	-	-	-	-	-
257	35	-	35	-	-	-	-	-	-
257A	-	-	-	-	-	-	-	-	-
258	36	36 & 37	36	-	-	-	-	-	-

* = FM Approved ■ = UL Listed ▲ = ULC Listed

Anvil Compliances, Listings and Approvals

(cont.)

Anvil Figure Number	Product Types			Application Sizes					
	MSS-SP-58 & MSS-SP-69	Federal Specifications		FM Rod Size	FM Pipe Size	UL Rod Size	UL Pipe Size	ULC Rod Size	ULC Pipe Size
		WW-H-171-E	A-A-1192A						
259	37	-	37	-	-	-	-	-	-
260	1	1	1	3/8	3/4 - 2	3/8	3/4 - 2	3/8	3/4 - 2
				1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2	1/2	2 1/2 - 3 1/2
				5/8	4, 5	5/8	4, 5	5/8	4, 5
				3/4	6	3/4	6	3/4	6
				7/8	8	7/8	8	7/8	8
261	8	8	8	-	-	N/A	1 1/2 - 8	N/A	1 1/2 - 8
262	26	26	26	-	-	-	-	-	-
264	38	39	38	-	-	-	-	-	-
265	38	39	38	-	-	-	-	-	-
271	44	45	44	-	-	-	-	-	-
274	46	47	46	-	-	-	-	-	-
274P	-	-	-	-	-	-	-	-	-
275	-	-	-	-	-	-	-	-	-
277	45	46	45	-	-	-	-	-	-
277S	-	-	-	-	-	-	-	-	-
278	-	-	-	-	-	-	-	-	-
278L	-	-	-	-	-	-	-	-	-
278X	-	-	-	-	-	-	-	-	-
281	18	19	18	3/8	3/4 - 4	3/8	3/4 - 4	3/8	3/4 - 4
				1/2	5 - 8	1/2	5 - 8	1/2	5 - 8
				5/8	8 MAX.	5/8	8 MAX.	5/8	8 MAX.
				3/4	8 MAX.	3/4	8 MAX.	3/4	8 MAX.
282	18	18	18	3/8	3/4 - 4	3/8	3/4 - 4	3/8	3/4 - 4
				1/2	5 - 8	1/2	5 - 8	1/2	5 - 8
				5/8	8 MAX.	5/8	8 MAX.	5/8	8 MAX.
				3/4	8 MAX.	3/4	8 MAX.	3/4	8 MAX.
284	-	-	-	7/8	8 MAX.	7/8	8 MAX.	7/8	8 MAX.
				-	-	-	-	-	-
				-	-	-	-	-	-
				-	-	-	-	-	-
285	19	18	18	3/8	3/4 - 4	3/8	3/4 - 4	3/8	3/4 - 4
				1/2	5 - 8	1/2	5 - 8	1/2	5 - 8
				5/8	8 MAX.	5/8	8 MAX.	5/8	8 MAX.
286	18	18	18	-	-	-	-	-	-
290	17	17	17	-	-	-	-	-	-
290L	17	17	17	-	-	-	-	-	-
291	-	-	-	-	-	-	-	-	-
292	28 & 29	28 & 29	28 & 29	-	-	-	-	-	-
292L	28 & 29	28 & 29	28 & 29	-	-	-	-	-	-
295	3	3	3	-	-	-	-	-	-
295A	3	3	3	-	-	-	-	-	-
295H	3	3	3	-	-	-	-	-	-
299	14	14	14	-	-	-	-	-	-
300	1	1	1	-	-	-	-	-	-
395	-	-	-	-	-	-	-	-	-
432	-	-	-	-	-	-	-	-	-
436	35	-	35	-	-	-	-	-	-
436A	-	-	-	-	-	-	-	-	-
439	35	-	35	-	-	-	-	-	-
590	1	1	1	-	-	-	-	-	-
594	-	-	-	-	-	-	-	-	-
595	8	-	8	-	-	-	-	-	-
599	-	-	-	-	-	-	-	-	-
600	8	-	8	-	-	-	-	-	-

* = FM Approved ■ = UL Listed ▲ = ULC Listed

Anvil Compliances, Listings and Approvals
(cont.)

Anvil Figure Number	Product Types			Application Sizes					
	MSS-SP-58 & MSS-SP-69	Federal Specifications		FM Rod Size	FM Pipe Size	UL Rod Size	UL Pipe Size	ULC Rod Size	ULC Pipe Size
		WW-H-171-E	A-A-1192A						
CT-65	-	12	-	-	-	-	-	-	-
CT-69	10	10	10	-	-	-	-	-	-
CT-99	9	9	9	-	-	-	-	-	-
CT-99C	9	9	9	-	-	-	-	-	-
CT-109	11	11	11	-	-	-	-	-	-
CT-121	8	8	8	-	-	-	-	-	-
CT-121C	-	-	-	-	-	-	-	-	-
CT-128C	-	-	-	-	-	-	-	-	-
CT-138R	12	25	12	-	-	-	-	-	-
CT-255	-	-	-	-	-	-	-	-	-

A type is dependent upon its appropriate installation and use.
 Note: Figure 218 Must be used with Figure 157.

Engineered Hangers - Compliances, Listings and Approvals

Anvil Figure Number	Product Types		
	MSS-SP-58 & MSS-SP-69	Federal Specifications	
		WW-H-171-E	A-A-1192A
170 - Horizontal Traveler	58	-	-
200, C-200, 201 and C-201 - Hydraulic Snubbers	47	-	-
210 - Replacement Strut	-	-	-
211, C-211, 640, C-640 - Sway Strut Assembly	-	-	-
222 and C-222 - Mini-Sway Strut Assembly	-	-	-
247 - Spring Cushion	48	49	49
296, C-296, 297, C-297, 298, C-298, 301, C-301 & 302 - Swing Sway Brace	50	55	55
312 - Tapered Pin	-	-	-
1306 and 1307 - Limit Stop	-	-	-
3306 & 3307 - Hydraulic Snubbers	47	-	-
Variable Spring Hangers			
82, B-268, 98, Triple, Quadruple Type A-E	51	51	51
C-82, C-268, C-98, Triple-CR, Quadruple-CR Type A-E	51	51	51
82, B-268, 98, Triple, Quadruple Type F	52	56	56
C-82, C-268, C-98, Triple-CR, Quadruple-CR Type F	52	56	56
82, B-268, 98, Triple, Quadruple Type G	53	57	57
C-82, C-268, C-98, Triple-CR, Quadruple-CR Type G	53	57	57
Constant Support Hangers			
80-V and C-80-V Type A-E	55	58	58
80-V and C-80-V Type G	56	59	59
81-H and C-81-H Type A-E	54	52	52

* = FM Approved ■ = UL Listed ▲ = ULC Listed